

(12) **UK Patent Application** (19) **GB** (11) **2 371 561** (13) **A**

(43) Date of Printing by UK Office 31.07.2002

(21) Application No 0128910.7

(22) Date of Filing 02.06.2000

(30) Priority Data

(31) 11156546

(32) 03.06.1999

(33) JP

(86) International Application Data

PCT/JP00/03604 Jp 02.06.2000

(87) International Publication Data

WO00/75400 Jp 14.12.2000

(51) INT CL⁷

C23G 5/032

(52) UK CL (Edition T)

C7E E172 E178 E192 E3B

(56) Documents Cited by ISA

JP 200001680 A

(58) Field of Search by ISA

JITSUYO SHINAN KOHO 1926-1996

JITSUYO SHINAN TOROKU KOHO 1996-2000

KOKAI JITSUYO SHINAN KOHO 1971-2000

(71) Applicant(s)

Nicca Chemical Co Limited
(Incorporated in Japan)

23-1 Bunkyo 4-Chome, Fukui-shi, Fukui 910-8670,
Japan

(74) Agent and/or Address for Service

Boult Wade Tennant

Verulam Gardens, 70 Gray's Inn Road, LONDON,
WC1X 8BT, United Kingdom

(72) Inventor(s)

Youichi Mukogawa
Yutaka Sano

(54) Abstract Title

Detergent composition for petroleum refining apparatus

(57) A detergent composition for petroleum refining apparatuses which is to be mixed with a petroleum solvent when the inside of a petroleum refining apparatus is cleansed with the solvent in the absence of water, characterized by containing a surfactant which has a solubility in gas oil at 25°C of 10 or higher. By using the detergent composition together with a petroleum solvent, the petroleum solvent rapidly penetrates into fouling ingredients to produce a sufficient cleansing effect. As a result, the cleansing efficiency can be significantly improved and the time required for cleansing the inside of a petroleum refining apparatus can be considerably shortened.

GB 2 371 561 A

DESCRIPTION

Detergent Composition for Petroleum Refining Apparatus

5 **Technical Field**

The present invention relates to a detergent composition for petroleum refining apparatus.

Background Art

10 As a petroleum refining apparatus is operated, heavy oil contents, which are generated when petroleum is partly polymerized upon heat, and soil components such as the sludge occurring upon deterioration (or degradation) of metals in the inner wall of the apparatus (hereinafter collectively referred to as "soil components") adhere to the inside of
15 heat exchangers, pipes, heating furnaces, desalters, and the like (hereinafter collectively referred to as "petroleum refining apparatus") constituting the apparatus.

 When such soil components accumulate within the
20 petroleum refining apparatus, the petroleum refining efficiency may lower. For preventing this from happening, the inside of the petroleum refining apparatus is periodically washed. As the washing method therefor, while water washing with a jet of water has widely been used in
25 general, methods in which an aqueous surfactant solution or a petroleum solvent is circulated within the petroleum

refining apparatus for washing have recently been proposed as a method for shortening the washing time.

Disclosure of the Invention

5 The above-mentioned method using an aqueous surfactant solution, however, tends to require enormous labor and cost for processing a large amount of waste water occurring upon washing. Also, its washing effects have not been proportionally efficient. In the above-mentioned method
10 using a petroleum solvent, on the other hand, the petroleum solvent does not sufficiently infiltrate into soil components which have become bulky as a result of deposition. Therefore, sufficient washing effects have not always been available. Hence, none of these methods has been able to achieve fully
15 satisfactory improvement of washing efficiency and shortening of washing time.

 In view of such circumstances, it is an object of the present invention to provide a detergent composition for petroleum refining apparatus, which can exhibit sufficient
20 washing effects when used together with a petroleum solvent and improve the washing efficiency, whereby the washing time within the petroleum refining apparatus can be shortened.

 The inventors have repeated diligent studies for solving the above-mentioned problem and, as a result, have
25 found that, when a specific surfactant is mixed into a petroleum solvent used for washing, the solubility of the

heavy oil contents and sludge into the petroleum solvent is improved, thus achieving the present invention.

Namely, the present invention provides a detergent composition for petroleum refining apparatus, which is used as being mixed with a petroleum solvent when the inside of a petroleum refining apparatus is washed with the petroleum solvent in a nonaqueous system, the detergent composition containing a surfactant having a solubility of at least 10 with respect to a diesel fuel at a temperature of 25°C.

In such a detergent composition for petroleum refining apparatus (hereinafter referred to as "detergent composition") in accordance with the present invention, the petroleum solvent containing the surfactant rapidly infiltrates into soil components due to the surface activity of the surfactant. This helps the heavy oil contents in soil components to dissolve into the petroleum solvent, and allows the solidified sludge in the soil components to favorably disperse into the petroleum solvent. As a result, the petroleum solvent exhibits sufficient washing effects, whereby the washing efficiency can be improved.

Also, since the surfactant is excellently good in its solubility to the petroleum solvent, it is mixed with the latter very well, whereby favorable surface active effects are exhibited. As a consequence, the washing efficiency can be improved remarkably.

Preferably, the detergent composition of the present

invention further contains a terpene compound. The terpene compound is a compound excellently good in dissolving the heavy oil contents contained in soil components, and also is excellent in compatibility with the surfactant. As a consequence, the soil components are fully dissolved into the detergent composition itself, and the surface activity of the surfactant is fully exhibited. Therefore, the washing efficiency is further improved.

In addition, since the terpene compound is excellent in compatibility with the surfactant, if the surfactant has a high viscosity, then mixing it with the terpene compound can lower the viscosity of the detergent composition. As a result, it becomes quite easy for the detergent composition to be injected into the petroleum refining apparatus.

More preferably, the content of the surfactant in the detergent composition is 5 to 80% by weight, whereas the content of the terpene compound in the detergent composition is 20 to 95% by weight, i.e., the mixing ratio of the surfactant and the terpene compound is 5:95 to 80:20 in terms of weight ratio.

If the mixing ratio of the surfactant and the terpene compound lies within such a range, then the petroleum solvent can be infiltrated into soil components more rapidly. Also, the solvent activity of the detergent composition itself can be prevented from lowering due to the relative decrease in the content of terpene compound.

More preferably, in the detergent composition in accordance with the present invention, the petroleum solvent is a light oil, and the above-mentioned detergent composition is dissolved into this petroleum solvent (light oil) by 0.5 to 20% by weight. In other words, the detergent composition of the present invention may be such that the above-mentioned detergent composition is added to a light oil as the petroleum solvent, whereas it is desirable that the ratio of addition be 0.5 to 20% by weight with respect to the light oil.

Maintaining the content (amount of use or amount of addition) of the detergent composition within such a range reliably helps the heavy oil contents in soil components to dissolve into the petroleum solvent. Also, in this case, the dispersion of the sludge contained in the soil components into the petroleum solvent can reliably be accelerated. Further, the washing efficiency can be prevented from being saturated, whereby washing effects matching the cost or higher can be obtained. Namely, it is advantageous in that the cost performance can be improved.

In the present invention, "diesel fuel" as a solvent for defining the solubility of surfactant is "type-I diesel fuel" defined by the Japanese Industrial Standard JIS K 2204(1997) "Diesel fuel". On the other hand, "solubility" of the surfactant with respect to the diesel fuel in the present invention is a value expressing in terms of grams the limit at which the surfactant transparently dissolves

in 100 g of the diesel fuel. Further, "light oil" in the present invention refers to, in petroleum distillates, light and medium distillates other than so-called heavy distillates (A to C heavy oils, residual oil), e.g., such as kerosene, gas oil, and LCO (Light Cycle Oil), which are petroleum distillates having a boiling point of 100 to 330°C.

Also, "nonaqueous system" means that water is not intentionally added thereto upon washing, and does not matter whether or not a water content exists in the soil compositions accumulated within the petroleum refining apparatus. Further, a slight water content may be mixed into the petroleum solvent due to a small water content contained in the detergent composition.

Best Modes for Carrying Out the Invention

In the following, preferred embodiments of the present invention will be explained. The detergent composition of the present invention contains a surfactant having a solubility of at least 10 with respect to a diesel fuel at a temperature of 25°C, and is used as being mixed with a petroleum solvent when the inside of a petroleum refining apparatus is washed with the petroleum solvent in a nonaqueous system.

The petroleum solvent may be any petroleum solvent as long as it can dissolve or disperse soil components, and a light oil can preferably be used, for example. If the

above-mentioned solubility of the surfactant is less than 10, then it tends to be harder to become fully compatible with the petroleum solvent, such as light oil in particular. In this case, there is a tendency that the dissolution of soil components into the light oil or the dispersion of the solidified sludge and the like contained in the soil components into the light oil is not effected favorably.

Examples of the above-mentioned surfactant include petroleum sulfonate, lecithin, sorbitan esters, aliphatic acid esters, alkyl ether nonions, alkylaryl ether nonions, and the like, whereas compounds or components belonging to them can be used separately or in a mixture of two or more species.

Among them, petroleum sulfonate is a sulfonic acid mixture of hydrocarbons generated as a by-product when refining petroleum distillates with sulfuric acid, or the like, for which Sulfol 400, 430, 465, and 500 (registered trade marks; manufactured by Matsumura Oil Co., Ltd.), for example, are commercially available.

Examples of lecithin include soybean lecithin, egg lecithin, and the like, in which soybean lecithin is preferable from the viewpoint of stability in supply in the market and cost efficiency. Also, soybean lecithin is particularly advantageous from the viewpoint of improving washing performances since it is excellent in the permeability to firmly attached soil components and the

dispersibility of sludge.

Examples of sorbitan esters include sorbitan monolaurate, sorbitan monooleate, sorbitan monostearate, sorbitan trilaurate, sorbitan trioleate, sorbitan
5 tristearate, and the like. Among them, sorbitan monooleate and sorbitan trioleate are preferably used. These are preferable from the viewpoint of improving washing performances, since they are easy to handle and are excellent in the permeability to firmly attached soil components and
10 the dispersibility of sludge.

Also namable as sorbitan esters are compounds in which an alkylene oxide having a carbon number of 2 to 4 is added to the above-mentioned sorbitan esters, whereas the amount of addition of alkylene oxide is preferably 1 to 3 mol. If
15 the amount of addition exceeds 3 mol, then its solubility to the petroleum solvent tends to decrease.

Among these sorbitan esters, a sorbitan ester having 1 to 2 mol of ethylene oxide added thereto is preferably used in particular, since it is quite effective in improving
20 the dispersion of the sludge content generated upon metal deterioration. It is assumed to be because of the fact that, since an appropriate amount of ethylene oxide is added thereto, a slight hydrophilic property of the sorbitan ester is appropriately enhanced to a small extent, whereby the
25 compatibility of the metal ion or metal compound in the sludge with the petroleum solvent is improved. Its effect is not

restricted thereto, however.

Examples of aliphatic esters include glycerin monolaurate, glycerin monopalmitate, glycerin monostearate, glycerin monooleate, glycerin dilaurate, glycerin dioleate, glycerin trioleate, and the like; vegetable oils such as castor oil, coconut oil, soybean oil, and rape-seed oil; or the like.

Among them, glycerin monooleate, glycerin dioleate, glycerin trioleate, and castor oil are preferably used. These are preferable from the viewpoint of improving washing performances, since they are easy to handle and are excellent in the permeability to firmly attached soil components and the dispersibility of sludge.

Further, as with sorbitan esters, also namable are compounds in which an alkylene oxide having a carbon number of 2 to 4 is added to the above-mentioned aliphatic acid esters, whereas the amount of addition of alkylene oxide is preferably 1 to 3 mol. If the amount of addition exceeds 3 mol, then its solubility to the petroleum solvent tends to decrease.

Among these aliphatic acid esters, an aliphatic acid ester having 1 to 2 mol of ethylene oxide added thereto is preferably used in particular, since it is quite effective in improving the dispersibility of the sludge content generated upon metal deterioration. As in the case of the above-mentioned sorbitan esters, it is assumed to be because

of the fact that a slight hydrophilic property of the aliphatic acid ester is appropriately enhanced to a small extent, whereby the compatibility of the metal ion or metal compound in the sludge with the petroleum solvent is improved. Its effect is not restricted thereto, however.

An example of the above-mentioned alkyl ether nonions is a compound in which 1 to 5 mol of an alkylene oxide having a carbon number of 2 to 4 are added to an alcohol having a carbon number of 10 to 18. Further, an example of alkylaryl ether nonions is a compound in which 1 to 5 mol of an alkylene oxide having a carbon number of 2 to 4 are added to octyl phenol or nonyl phenol.

Among these surfactants, as the sorbitan esters, aliphatic acid esters, alkyl ether nonions, and alkylaryl ether nonions, those preferably having a hydrophilic-lipophilic balance value (hereinafter referred to as "HLB value") of 1 to 10 are suitable.

If the HLB value of the surfactant is less than the lower limit of the above-mentioned range, then its affinity with the hydrophilic ingredients in the soil components (e.g., metals, metal compounds, and the like in the sludge) tends to become insufficient. If the HLB value exceeds the upper limit of the above-mentioned range, then its dissolution into the petroleum solvent and terpene compounds, which will be explained later, tends to become insufficient. The HLB value herein refers to Griffin's HLB value (ditto in the

following).

Preferably, the detergent composition of the present invention further contains, in addition to the above-mentioned surfactant, a compound which can dissolve heavy oil contents. As such a compound, terpene compounds are particularly preferable from the viewpoint of its compatibility with the surfactant.

Examples of terpene compounds include monoterpene compounds, sesquiterpene compounds, diterpene compounds, triterpene compounds, and the like, among which monoterpene compounds are preferable.

Examples of monoterpene compounds include terpene hydrocarbons such as d-limonene, hydrogenated limonene, β -pinene, myrcene, camphene, tricyclene, and terpinolene; and terpene alcohols such as linalool, myrcenol, menthol, geraniol, terpineol, borneol, and hydrogenated terpineol. Among these terpene compounds, one species may be used alone, or two or more species may be used in combination.

Preferable among these terpene compounds is d-limonene, which is excellent in improving the solubility of the petroleum solvent. Further, if high-temperature washing is carried out by using a petroleum solvent having a higher boiling point, then the viscosity of soil components decreases, so that the firmly attached soil components become easier to peel off, and the dissolution and dispersion of soil components into the petroleum solvent are accelerated.

It is desirable for the surfactant and terpene compounds employed in this case to have a boiling point of at least 150°C.

5 More preferably, the content of the above-mentioned surfactant in the detergent composition is 5 to 80% by weight, whereas the content of the terpene compound therein is 20 to 95% by weight. Namely, it is further preferred that the mixing ratio of the surfactant and the terpene compound is 5:95 to 80:20 in terms of weight ratio.

10 If this mixing ratio is less than 5:95, then there is a tendency that the petroleum solvent is less likely to rapidly infiltrate into the soil components due to the shortage of surfactant. If the mixing ratio exceeds 80:20, on the other hand, then, though the surface activity is enhanced thereby,
15 the amount of terpene compound relatively decreases, so that the solvent effect of the detergent composition itself lowers. As a result, washing effects tend to be saturated.

20 More preferably, the detergent composition of the present invention is constituted by a light oil and 0.5 to 20% by weight of the above-mentioned detergent composition dissolved therein. Namely, the detergent composition in accordance with the present invention may comprise a light oil having the above-mentioned detergent composition added thereto, whereas the ratio of addition is desirably 0.5 to
25 20% by weight with respect to the light oil.

If the amount of use (ratio of addition) of the detergent

composition is less than 0.5% by weight, then it becomes harder for the petroleum solvent to sufficiently infiltrate into soil components, and there is a tendency that the dissolution and dispersion of the petroleum solvent into the soil components are not fully enhanced. If the amount of use exceeds 20% by weight, on the other hand, then the washing efficiency tends to be substantially saturated though being somewhat enhanced, whereby washing effects matching the cost or higher may not be obtained.

An example of the method (procedure) of washing the petroleum refining apparatus by use of the detergent composition in accordance with the present invention is a procedure as follows. First, a petroleum solvent is put into a mixing bath, and the detergent composition of the present invention is added to the mixing bath so as to attain a predetermined concentration range. Subsequently, these are mixed well, so that the detergent composition is dissolved in the petroleum solvent (the resulting mixed liquid also becoming the detergent composition of the present invention if the amount of addition of the detergent composition is within the preferable range mentioned above). The petroleum solvent containing the detergent composition is further heated, and then is injected into the petroleum refining apparatus to be washed. Thereafter, the petroleum solvent is circulated within the petroleum refining apparatus with a pump or the like.

As another procedure, in a state where a predetermined amount of a heated petroleum solvent is injected into and circulated within the petroleum refining apparatus beforehand, the detergent composition of the present invention may additionally be injected into the petroleum refining apparatus by an amount residing within a predetermined concentration range.

According to such a detergent composition of the present invention, the surface activity of the surfactant causes the petroleum solvent to rapidly infiltrate into soil components, which helps heavy oil contents in the soil components to dissolve into the petroleum solvent and allows the sludge in the soil components to favorably disperse into the petroleum solvent. Therefore, the petroleum solvent exhibits sufficient washing effects, so that the washing efficiency can be improved. As a result, the washing time can be made shorter than that conventionally attained.

Also, since the surfactant is excellently good in its solubility with respect to light oils such as kerosene, it can be mixed with the petroleum solvent very well, whereby the washing efficiency can be enhanced remarkably. As a consequence, the washing time can be shortened greatly.

If the detergent composition further contains a terpene compound, since the terpene compound is excellently good in the capability of dissolving the heavy oil contents and the like contained in soil components and also is excellent

in the compatibility with the surfactant, the soil components can fully be dissolved into the detergent composition itself. Then, the surfactant can fully exhibit its surface activity. As a consequence, the washing efficiency can further be improved, whereby the washing time can drastically be shortened.

Also, since the terpene compound is excellent in compatibility with the surfactant, if the surfactant has a high viscosity, then mixing it with the terpene compound can lower the viscosity of the detergent composition. As a result, it becomes quite easy for the detergent composition to be injected into the petroleum refining apparatus, whereby the operability upon washing can be improved.

Further, if the surfactant and terpene compound having a boiling point of 150°C or higher are used, then high-temperature washing can be effected by use of a petroleum solvent having a high boiling point. As a consequence, the viscosity of soil components can be lowered, whereby the firmly attached soil components become easier to peel off, and the dissolution and dispersion of soil components into the petroleum solvent are accelerated. Therefore, the washing efficiency can further be improved.

In addition, since the mixing ratio of the surfactant and terpene compound in the detergent composition is 5:95 to 80:20 in terms of weight ratio, the petroleum solvent can further rapidly be infiltrated into the soil components.

Also, the solvent activity of the detergent composition itself can be prevented from lowering due to the relative decrease in the amount of terpene compound. As a result, the solubility of the detergent composition with respect to the soil components and the surface activity of the surfactant can fully be exhibited. As a consequence, the washing efficiency can further be improved.

In the case where the detergent composition is dissolved (added) into the petroleum solvent by 0.5 to 20% by weight, it reliably helps heavy oil contents in soil components to dissolve into the petroleum solvent. Also, it can reliably accelerate the dispersion of the sludge contained in the soil components into the petroleum solvent. These can reliably achieve a sufficient washing efficiency. Further, since the washing efficiency can also be prevented from being saturated, washing effects matching the cost or higher are obtained.

Examples

In the following, the present invention will be explained in further detail with reference to Examples, which do not restrict the present invention.

Making of Test Piece

Assuming that the soil components adhering to the inside of the petroleum refining apparatus subjected to washing in practice were various, test pieces with various amounts of adhesion of asphalt (soil component) were manufactured

as follows.

First, a plurality of cold-rolled steel plates (50 mm x 25 mm x 1.6 mm thickness) coated with 0.1 g of asphalt were prepared. They were placed on a hot plate at 350°C, so as to be subjected to baking for 1 min, 5 min, and 10 min, respectively, whereby three kinds of test pieces were obtained. (Washing seems to become more difficult as the baking time is longer, since the asphalt content is more solidified.) In the following, those with the baking times of 1 min, 5 min, and 10 min will be referred to as test pieces (1), (2), and (3), respectively.

Also, the dry weight of each test piece was measured before being coated with asphalt and after being coated with asphalt and baked, and the difference between thus measured values was taken, whereby the weight W1 of asphalt attached to the test piece was determined.

Washing Test

First, a diesel fuel (gas oil) or kerosene having the detergent composition added thereto or a diesel fuel (gas oil) alone (100 cc each) and one sheet of test piece were put into a metal pot (with a volume of 120 cc). After being closed, the metal pot was put into a thermostat bath at 130°C. Subsequently, the metal pot was held within the thermostat bath for 1 to 3 hr while in a state where the metal pot was horizontally rotated so as to generate a liquid flow within the metal pot. Thereafter, the metal pot was removed from

the thermostat bath, and the test piece was taken out therefrom. Further, after the superfluous oil content attached thereto was wiped off, the test piece was dried for 1 hr with a drier at 180°C.

5 After cooling, the weight of the test piece was measured. From the difference between this weight and the dry weight of the test piece before being coated with asphalt measured in "Making of Test Piece" mentioned above, the weight W2 of asphalt remaining in the test piece after washing was
10 calculated. Then, the washing ratio was calculated by the following relational expression (1):

$$\text{washing ratio}(\%) = 100 - (W2/W1) \times 100 \quad \dots (1)$$

Examples 1 to 10

15 The surfactants (whose details are shown in Table 2) and terpene compounds shown in the following Table 1 were mixed at the compounding ratios shown in Table 1, whereby detergent compositions of Examples 1 to 10 were obtained.

TABLE 1

	Composition and compounding ratio of detergent composition (terpene compound/surfactant = wt%/wt%)
Example 1	d-limonene/petroleum sulfonate = 50/50
Example 2	d-limonene/soybean lecithin = 50/50
Example 3	d-limonene/sorbitan trioleate = 50/50
Example 4	d-limonene/castor oil = 50/50
Example 5	d-limonene/petroleum sulfonate = 70/30
Example 6	d-limonene/soybean lecithin = 60/40
Example 7	β -pinene/soybean lecithin = 50/50
Example 8	β -pinene/sorbitan trioleate = 30/70
Example 9	none/soybean lecithin = 0/100
Example 10	none/sorbitan trioleate = 0/100

TABLE 2

	Product used	Solubility to diesel fuel (25°C)	HLB value
Petroleum sulfonate	Sulfol 500 (made by Matsumura Oil Co., Ltd.)	30 or more	—
Soybean lecithin	Lecithin DX (made by Nisshin Oil Mills, Ltd.)	30 or more	—
Sorbitan trioleate	—	30 or more	1.8
Castor oil	Refined castor oil (made by Itoh Seiyu K.K.)	30 or more	—

Results of Washing Test

The detergent compositions obtained by Examples 1 to 10 were added and dissolved into a diesel fuel (gas oil) or kerosene acting as the petroleum solvent, so as to attain concentrations shown in Table 3, and the above-mentioned test pieces were washed with thus obtained detergent composition solutions. Table 3 shows thus obtained results.

TABLE 3

	Test piece	Petroleum solvent	Detergent composition	Added amount	Washing time	Washing ratio
Washing Example 1	(2)	diesel fuel	Example 1	5 %	1 hr	70 %
Washing Example 2	(2)	diesel fuel	Example 2	5 %	1 hr	72 %
Washing Example 3	(2)	diesel fuel	Example 3	5 %	1 hr	69 %
Washing Example 4	(2)	diesel fuel	Example 4	5 %	1 hr	64 %
Washing Example 5	(2)	diesel fuel	Example 5	5 %	1 hr	71 %
Washing Example 6	(2)	diesel fuel	Example 6	5 %	1 hr	73 %
Washing Example 7	(2)	diesel fuel	Example 7	5 %	1 hr	66 %
Washing Example 8	(2)	diesel fuel	Example 8	5 %	1 hr	65 %
Washing Example 9	(2)	diesel fuel	Example 9	5 %	1 hr	62 %
Washing Example 10	(2)	diesel fuel	Example 10	5 %	1 hr	60 %
Comparative Washing Example 1	(2)	diesel fuel	—	—	1 hr	47 %
Washing Example 11	(3)	diesel fuel	Example 2	3 %	2 hr	52 %
Washing Example 12	(3)	diesel fuel	Example 3	3 %	2 hr	50 %
Comparative Washing Example 2	(3)	diesel fuel	—	—	2 hr	34 %
Washing Example 13	(1)	kerosene	Example 1	10 %	1 hr	99 %
Washing Example 14	(1)	kerosene	Example 1	10 %	2 hr	100 %
Washing Example 15	(1)	kerosene	Example 1	10 %	3 hr	100 %

5 In Table 3, Washing Examples 1 to 15 relate to the results of washing test pieces by use of the detergent compositions of Examples 1 to 10, whereas Comparative Washing Examples 1 and 2 relate to results of washing test pieces by use of a petroleum solvent alone.

First, Comparative Washing Example 1 and Washing Examples 9 and 10 each using test piece (2) were compared with each other. As a result, while the washing ratio of Comparative Washing Example 1 was 47%, the respective washing ratios in Washing Examples 9 and 10 were 60% and 62%, whereby a significant improvement in washing ratio due to Examples was seen. From this result, it has been verified that washing performances are clearly improved when a diesel fuel (gas oil; petroleum solvent) mixed with a detergent composition containing soybean lecithin (surfactant) is used, as compared with the conventional case of washing with the diesel fuel (gas oil) alone.

Also, Washing Examples 1 to 8 including terpene compounds exhibited washing ratios with further higher values of 64% to 73%. From this result, it has been verified that washing effects are remarkably improved when a diesel fuel (gas oil; petroleum solvent) mixed with a detergent composition containing a surfactant and a terpene compound is used, as compared with the conventional case using the diesel fuel (gas oil) alone.

Next, Comparative Washing Example 2 and Washing Examples 11 and 12 each using test piece (3) were compared with each other. As a result, while the washing ratio of Comparative Washing Example 2 was 34%, the respective washing ratios in Washing Examples 11 and 12 were 52% and 50%. From this result, it has been verified that the diesel fuel (gas

oil; petroleum solvent) mixed with the detergent composition of the present invention also exhibits favorable washing effects with respect to asphalt (soil component) having a very high degree of adherence.

5 Also, the washing ratio in Washing Examples 13 to 15 using test piece (1) was 99% to 100%. From this result, it has been verified that the kerosene (petroleum solvent) mixed with the detergent composition of the present invention can substantially completely eliminate asphalt (soil component) having a low degree of adherence.

10 From these test results, it is understood that, when the detergent composition in accordance with the present invention is used together with the petroleum solvent, sufficient washing effects can be obtained independently of the degree of adherence of soil components, i.e., with respect to various modes of attachment of soil components.

Industrial Applicability

15 As explained in the foregoing, the detergent composition for petroleum refining apparatus of the present invention can exhibit sufficient washing effects when used together with a petroleum solvent, so as to remarkably improve the washing efficiency, thereby making it possible to greatly shorten the washing time within the petroleum refining apparatus.

CLAIMS

1. A detergent composition for petroleum refining apparatus, which is used as being mixed with a petroleum solvent when the inside of a petroleum refining apparatus is washed with said petroleum solvent in a nonaqueous system,
5 said detergent composition containing a surfactant having a solubility of at least 10 with respect to a diesel fuel at a temperature of 25°C.

2. A detergent composition for petroleum refining apparatus according to claim 1, further containing a terpene compound.
10

3. A detergent composition for petroleum refining apparatus according to claim 2, wherein said surfactant has a content of 5 to 80% by weight in said detergent composition for petroleum refining apparatus, and
15

wherein said terpene compound has a content of 20 to 95% by weight in said detergent composition for petroleum refining apparatus.

4. A detergent composition for petroleum refining apparatus, wherein said petroleum solvent is a light oil, and
20

wherein 0.5 to 20% by weight of the detergent composition for petroleum refining apparatus according to one of claims 1 to 3 is dissolved in said light oil.
25

5. A detergent composition as claimed in claim 1 substantially as hereinbefore described with reference to and as illustrated in the Examples.

INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP00/03604

A. CLASSIFICATION OF SUBJECT MATTER
Int.Cl.⁷ C23G 5/032

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

Int.Cl.⁷ C23G 5/032

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched
Jitsuyo Shinan Koho 1926-1996 Jitsuyo Shinan Toroku Koho 1996-2000
Kokai Jitsuyo Shinan Koho 1971-2000

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A P	JP, 2000-1680, A (Sofutado Kogyo K.K.), 07, January, 2000 (07.01.00). (Family: none)	1-4

☐ Further documents are listed in the continuation of Box C.☐ See patent family annex.

* Special categories of cited documents:
"A" document defining the general state of the art which is not considered to be of particular relevance
"E" earlier document but published on or after the international filing date
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
"O" document referring to an oral disclosure, use, exhibition or other means
"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"&" document member of the same patent family

Date of the actual completion of the international search
27 July, 2000 (27.07.00)Date of mailing of the international search report
08 August, 2000 (08.08.00)Name and mailing address of the ISA/
Japanese Patent Office

Authorized officer

Facsimile No.

Telephone No.